



Holly Ridge LED Post Top Lantern

Historic Series, HR20

PRODUCT OVERVIEW

The Holly Ridge LED Post Top Lantern combines aesthetics and installer-friendly features for roadway, area, and walkway lighting projects. The IP66 sealed LED light engine offers excellent optical control and heat dissipation for long life. Open frame full cutoff optics control glare and optional opal LumaLens provides soft illumination for adjacent building façade and landscape elements. The classic traditional Colonial styled lantern provides delivered lumens exceeding typical 150W HPS fixtures. Holly Ridge is perfect for multi-family residential projects, residential and Town Center streets, and historical themed commercial projects.



LEDicated *SoftLED*



Wall Mount



Pendant Mount

Inquire about Rapid Ship
813-855-9416

CONSTRUCTION

Diecast aluminum lantern 16" square x 16.75" H, 24.25" overall height

Diecast aluminum slip fitter for 3" x 3" tenon

Nickel plated stainless steel hardware

LIGHT ENGINE

LED array is mounted in an IP66 sealed rotatable Light Engine with integral diecast aluminum heat sink

30-80 Array watts – 4,800 to 11,500 delivered lumens, 3K, 4K, 5K CCT

IP67 fully potted 120-277VAC or 347-480VAC driver

OPTICS

Light Engine includes Integral Optics polycarbonate lens, IES Types I, II, III, IV and V

Lensed models include one-piece polycarbonate clear or opal LumaLens options

Open frame has zero upright to minimize light pollution and protect the night skies

MOUNTING

Post Top Tenon

Wall Mount with cast aluminum decorative bracket

Pendant mount

OPTIONS

Twist-lock photocell

Fusing and surge protection

Battery backup (up to 60 watts)