



EasyLED Step Light STP10Q

PRODUCT OVERVIEW

The Recessed STP10 Step Light luminaire provides low level shielded output for illumination of steps and walkways. The light engine is mounted in a baffled flush rectangular opening to maximize light levels on the walking path with minimal glare from the fixture. The internal die cast aluminum heatsink and IP66 sealed housing combined with long-lasting LED lifespan provides architectural accent lighting for years maintenance free service.



Black




White



Bronze



The die cast aluminum housing is finished with a weather-resistant textured powdercoat finish providing years of service. The 4-watt LED light engine utilizes a frosted tempered glass lens with silicone gaskets that meets IP66 sealing criteria. The fixture is designed to fit into a standard single gang junction box and mounts with (2) 1-1/2" – 6-32 Philips bevel head stainless steel screws. The 4-Watt LED array is available in 4000K CCT and is designed to replace outdated halogen and compact fluorescent systems with an energy savings of up to 80%.



Inquire about Rapid Ship
813-855-9416

CONSTRUCTION

- Die cast aluminum
- Frosted tempered glass lens
- Textured architectural black, bronze, and white powdercoat finish
- Fully shield glare free optics
- IP66 Sealed housing

LED

- 4-Watt 4000k CCT Standard
- Excellent thermal management for LED longevity
- 80% energy savings over halogen or compact fluorescent

DRIVER

- 120V, 50/60Hz, integral on-board design
- Non-dimming driver

APPLICATIONS

- Retail Centers
- Restaurants
- Hotels
- Schools & Universities
- Office Buildings
- Medical Facilities

MOUNTING

- Mounts into recessed single-gang junction box
- Provided with two 1½"-6-32 Philips bevel head stainless steel screws.

Catalog Number: STP10QF1X41204K* (*B=Black, Z=Bronze, W=White)

In Stock Now

12802 Commodity PL , Tampa, FL 33626 | Phone: 813-855-9416 | www.qssi.com